



SP-24

Loop Pad



Operating Instructions

CAUTIONS AND WARNINGS



IMPORTANT:

If the equipment is used in a manner not specified in this manual, the protection provided by the equipment may be impaired.

This product is an accessory or part of a system. Always read and follow the manufacturer's instructions for the equipment before connecting this product. Comply with all applicable codes and safety regulations. Failure to do so may result in damage, injury or death.

PRODUCT OVERVIEW

This product is designed for use with the EMX D-TEK loop detectors in a carwash environment. The proper location is between the rails where product cannot be struck or driven over.

Note: Walking on the unit may cause the wires to flex causing detection. Steel arch supports or Steel toe shoes may also cause the detector to output a detect signal. Tires or other objects striking the SP-24 may cause it to detect and or cause damage to the pad.

Specifications

Size	23.5 in x 23.5 in x 1.0 in
Material	Black Polypropylene
Connections	50 Foot 2 conductor lead wire
Detection Range	~ 30 inches
Accessories	SP-24 Guard 24 in x 3 in x 0.5 in



INDUSTRIES, INC.

4564 Johnston Parkway
Cleveland, Ohio 44128
United States of America
WEB <http://www.emxinc.com>

Sales Support
Telephone (216) 518-9888
Fax: (216) 518-9884

E-mail
salesupport@emxinc.com
Telephone (216) 518-9888

Technical Support
Telephone (216) 834-0761
E-Mail: technical@emxinc.com

