

CNTX-30-T

CONTRAST SENSOR

Increase process throughput with high-speed, accurate and reliable contrast differentiation. The CNTX™ combines a broad-spectrum light source, small spot size and fast response to achieve high-speed contrast differentiation of both neutral and color targets. The CNTX employs our field-proven, patented technology, for effective detection of registration marks, glossy surfaces, cap inserts, date codes and sorting of product by color in many industrial applications. The metal alloy case and glass lens provide robust construction expected in an industrial environment.

The CNTX provides simple, two-button teach with mark and background keys. The flexibility of the CNTX makes it easy to set-up in a wide variety of printing, packaging and converting applications. The CNTX is a perfect fit for many applications that require the ability to differentiate between two conditions that vary in contrast.

The CNTX includes both a discrete PNP/NPN output and an analog output. The discrete output is automatically set for PNP or NPN operation. The analog output signal may be used to access targets based on their reflectance characteristics.

CNTX



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com

www.emxinc.com

Applications

- Sort products by color
- Detect registration marks
- Confirm presence of date codes
- Detection of glossy surfaces
- Detects cap inserts

Design & Features

- 3.0mm spot size
- 25uS response time
- Two-button teach
- Broad spectrum white LED
- Automatic LED intensity adjustment
- PNP/NPN
- Discrete output
- Analog output
- Small size

Ordering Information



CNTX-30-T
Contrast Sensor

Accessories



UVX-300B
Bracket



UVX-300C
Cable 5P, 5M, M12, F

NOT INTENDED FOR USE IN
PERSONAL SAFETY APPLICATIONS.

Functions

OPERATING MODE
MARK
BACKGROUND
RED LED ON
GREEN LED ON
YELLOW LED ON
RED FLASHING
GREEN FLASHING
YELLOW FLASHING

The CNTX-30-T is in operating mode in detect or undetect state
Sets mark level
Sets background level
Mark detected
Background detected
Mark or background measurement in progress
Background set, measure mark
Mark set, measure background
Insufficient contrast

Specifications

White Light source

Sensing distance
Spot size
Depth of field
Response time
Switching Frequency
LED intensity
Sensitivity
Digital Output
Security

Background indicator
Detect indicator
Programming indicator
Data retention
Dimensions
Weight
Supply Voltage
Operating Current
Short Circuit Protection
Overload / Reverse Polarity Protection
Operating temperature
Storage temperature
Housing
Mechanical Protection

Broad spectrum LED,
min. 100,000 hours
28mm
3.0mm dia.
+/- 3mm
25uS
40kHz
3 levels
1X, 10X
Auto-Detect NPN/PNP
LOCK/UN-LOCK keypad
Green LED
Red LED
Yellow LED
EEPROM non—volatile memory
2.0" (51mm) x 2.4" (61mm) x 1.0" (25mm)
0.21 lbs. (95g)
10-24 VDC
60 mA
Discrete output
Supply voltage
-20°C...55°C
-20°C...70°C
Metal alloy
IP67 NOT FOR PRESSURE WASH DOWN

Indicators

Green LED Power
Red LED Detect
Yellow LED Program

Connector M12

Pin 1 Power 10 to 24VDC
Pin 2 Analog output 0 to 5V DC
Pin 3 Ground
Pin 4 Discrete output PNP/NPN
Pin 5 Remote LOCK/ UNLOCK input

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of manufacture. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship.